

Cutting table

Type	Auger
Width	1,5 / 2,0 / 2,3 m
Floatation	Accumulator
Height adj.	Hydraulic

Reel

Diameter	1,05 m
Speed range	15 ... 49 rpm
Speed adjustment	Stepless, electrical
Horizontal adjustment	Electrical

Threshing cylinder

Diameter	500 mm
Width	780 mm
Number of rasp bars	7
Speed range	400 - 500 rpm
optional	300 - 700 rpm
Speed adjustment	Stepless, electrical

Concave

Number of rasp bars	12
Length	490 mm
Angle of wrap	108°
Adjustment	Manual

Straw walkers

Number of walkers	3
Area	1,4 m ²

Grain tank

Capacity	1,5 m ³
Unloading height	2,8 m
Weighing hopper	70 l

Top sieve

Area	0,7 m ²
Type	Adjustable

Engine

Type	Detroit Diesel Turbo
Power	61 kW / 82 HP (DIN)
Cylinders	4
Fuel tank	140 l

Transmission

Type	Hydrostatic
Ground speed	
1.	0 - 5,0 km / h
2.	0 - 7,5 km / h
3.	0 - 20 km / h

Tyres

Front	12.4 R 24
Rear	11.5 - 15.3

Dimensions

Length, table attached	6 400 mm
Width	2 500 mm
Height with cab	3 300 mm
W / out cab	3 100 mm
Ground clearance	360 mm
Wheel base	1 900 mm
Wheel-track front	1 400 / 1 570 mm
Wheel-track rear	1 265 mm
Turning radius	3 500 mm
Weight*	3 400 kg

Accessories:

- Air condition
- Bottom sieve:
 - interchangeable round hole sieve 0,47 m²
- Four Wheel Drive
- Bagging device
- Weighing device

Specifications are subject to change and may vary from country to country. Manufacturer reserves right to do changes on products and specifications without any notice and without obligation to do such changes to machines manufactured earlier. All data should be regarded as approximation and cannot contain the special equipment which forms part of the machine in its standard version.

* Depending of the table



SAMPO-ROSENLEW LTD
 P.O. BOX 50, FIN-28101
 PORI, FINLAND
 Tel. +358 207 550 555
 Fax. +358 2 632 6546
 www.sampo-rosenlew.fi